

# MC80

## TRACKED CONVEYOR



### CONVEYOR

<b>Conveyor length working at 24°:</b>	21.4m (70'3")
<b>Belt width:</b>	1050mm (42")
<b>Drive drum dia:</b>	286mm (11.3")
<b>Tail drum dia:</b>	270mm (10.6")
<b>Capacity:</b>	Up to 500tph (551 US tph) depending on application Hydraulic folding head section

### POWER

<b>Tier 3:</b>	Deutz D2011 L041 36.4kW (48hp) @ 2200rpm
<b>Tier 4F / Tier V:</b>	Deutz TC 2.9 L04 45kW (60hp) @ 2200rpm

### FEEDBOOT

<b>Capacity:</b>	0.6 m <sup>3</sup> (0.8 yd <sup>3</sup> )
------------------	---

### TRANSPORT (Dimensions)

<b>Type:</b>	Self powered, fully containerised
<b>Length :</b>	11.88m (38' 11")
<b>Width :</b>	2.88m (9' 5")
<b>Height :</b>	2.25m (7' 4")
<b>Weight(estimated):</b>	16,750kg (36,927lbs)

### CURRENT OPTIONS

- 6mm AR400 steel wear feedboot liners
- 20mm rubber wear feedboot liners
- Feedboot extension c/w steel wear liners
- Feedboot extension c/w 20mm rubber wear liners
- Feedboot extension c/w 6mm AR400 steelwear liners
- Impact rollers at feedboot area

*\*Additional options available upon request*