

MT13R



HOPPER / FEEDER

Hopper type:	Fixed feed hopper, with optional manual extensions
Hopper capacity:	6m ³ (7.84 yd ³) / 10m ³ (13 yd ³)
Hopper body:	Abrasion resistant feed hopper with optional extension available
Feed apron conveyor:	1300mm (51")

ROLLER GRIZZLY

Gap setting range:	40mm - 110mm
Configuration:	1 set of 8 or 10 rollers 2 sets of 8 (standard) or 10 rollers 2 sets of 5 rollers

OUTPUT POTENTIAL

Up to 600tph / 661 US tph depending on application

POWER UNIT

Tier 3 / Tier 4F / STAGE V:	Volvo TAD883VE / CAT C9 (up to 310kW / 415hp)
------------------------------------	--

CONVEYORS

Apron conveyor width:	1300mm (51")
Discharge height:	4.9m – 6m (16' – 19' 8")

TRANSPORT (Dimensions)

Length:	1 roller configuration: 16m - 18m (52' 6" – 59') 2 roller configuration: 20m - 24m (65' 7" – 78' 9")
Width:	3.4m (10')
Height:	4.1m (11' 9")
Weight operating:	81,000 - 92,000Kg (178,574 – 202,825lbs)
Weight transport:	75,000 - 90,000kg (165,346– 291,620lbs)