

MT170I



HOOPER / FEEDER

Hopper type:	Fixed feed hopper or hydraulically foldable locking from ground level
Hopper capacity:	9m ³ (11.8 yd ³) / 18m ³ (23.5 yd ³)
Hopper body:	Abrasion resistant feed hopper with optional extension available

PRE-SCREEN (OPTIONAL)

Screen type:	Double deck
Dimensions:	1670mm x 3300mm (65" x 130")

IMPACT CRUSHER

Crusher inlet:	1670mm x 925mm (66" x 36")
Rotor diameter:	1300mm (51")
Rotor diameter optional:	1400mm (55")

OUTPUT POTENTIAL

Up to 1100tph / 1232 US tph depending on application

POWER UNIT

Tier 3 / Tier 4F / STAGE V:	CAT C18 / SCANIA DC16 (up to 565kW / 750hp)
------------------------------------	--

CONVEYORS

Product conveyor width:	1800mm (71")
Discharge height:	3.8m – 6.0m (12' 5" – 19' 7")

TRANSPORT (Dimensions)

Length:	20m-24m (65' 7" - 78' 8") depending on configuration
Width:	3.6m (11' 9")
Height:	4.2m (19' 9")
Weight operating:	87,000 - 96,000kg (191,802 – 211,643lbs)
Weight transport:	74,000 - 90,000kg (163,142 – 198,416lbs)