

# MT620HR



## HOPPER / FEEDER

- Hopper type:** Direct feed hopper with impact bars & rollers
- Hopper capacity:** 4.33m<sup>3</sup> (5.67 yd<sup>3</sup>)
- Hopper body:** Replaceable wear resistant steel panel liners

## SCREENBOX

- 6100mm x 1930mm (20' x 6' 4") triple deck screen
- Adjustable stroke angle & speed
- Wide range of screen media
- Max feed size up to 250mm
- Total screening area:** 35.3m<sup>2</sup> (380ft<sup>2</sup>)

## OUTPUT POTENTIAL

Up to 800 tph / 881 US tph depending on application

## POWER UNIT

- Tier 3 / Tier 4F / STAGE V:** CAT C7.1 151 kW (202hp) @ 2200rpm

## CONVEYORS

- Wide underscreen conveyor:** 1500mm (60")
- Wide finesize side conveyor:** 900mm (36")
- Wide mid-finesize:** 900mm (36")
- Wide oversize side conveyor:** 900mm (36")
- Wide mid-oversize tail conveyor:** 900mm (36")
- Wide oversize recirculating conveyor (optional):** 800mm (32")

## TRANSPORT (Dimensions)

- Length:** 19.54m (64' 1")
- Width:** 3.24m (10' 8")
- Height:** 3.6m (11' 10")
- Weight:** 46,700kg (102,955lbs)